



MACCO ORGANIQUES INC.

100 McArthur, suite 112, Valleyfield, Quebec, Canada, J6S 4M5

Tel: (450) 371-1066, Fax: (450) 371-5519

Web page address: www.macco.ca, Email: macco@macco.ca



THE MANUFACTURING PROCESS OF THE PRODUCT BELOW IS COVERED BY A REGISTERED ISO 9001 QUALITY SYSTEM AND A FSSC 22000 FOOD SAFETY SYSTEM

Date: December 01, 2017

Supersedes: October 17, 2017

Ref #: S50222-A-G

DC #: 17-273

SPECIFICATIONS SODIUM PROPIONATE NF AGGLOMERATE

GENERAL

Molecular formula: $C_3H_5NaO_2$

CAS #: 137-40-6

Molecular weight: 96.06

Description

White granular powder that is hygroscopic in moist air.

Parameters

Specifications

Identification

Passes test

Assay (anhydrous basis)

99.0 to 100.5%

Water

1.0% Max.

Heavy metals (as Pb)

10 ppm Max.

Alkalinity

Passes test

OVI and RS: This material conforms to the USP<467>, ICH Q3C and EP 5.4 requirements for organic volatile impurities (OVI) and residual solvents (RS). Based on our knowledge of the manufacturing process and on controlled handling and storage of the material, we acknowledge that there is no potential for introduction of residual solvents or organic volatile impurities in the product because the only solvent in our inorganic synthesis process is water.

Typical bulk density (tapped)

24 to 28 lbs/cu.ft.

0.38 to 0.45 g/mL

Typical particle size

On 850 μm (US std mesh #20): 1% Max.

Through 75 μm (US std mesh #200): 3% Max.

Packaging

20 kg multiwall paper bags

Storage

Store in a cool and dry place, in tight containers, for up to 2 years.

Conforms to current National Formulary (NF) requirements.

Liability: The information submitted in this document is based on current knowledge and experience. The information contained herein is furnished without warranty of any kind. Macco Organiques Inc. does not accept any liability whatsoever in respect of the use of this information nor in respect of use, application, adaptation or processing of the product described herein. The recommended times presented in this document may vary greatly depending on storage conditions.